

目 录

华翰物流API文档

版本信息

公共请求参数

createOrder (创建订单)

batchCreateOrder (批量创建订单)

getCargoTrack (轨迹查询)

modifyOrderWeight (修改订单重量)

getTrackNumber (查询跟踪号)

getShippingMethod (获取配送方式)

getLabelUrl (获取标签)

batchGetLabelUrl (批量获取标签)

cancelOrder (取消订单)

getOrder (查询订单)

feeTrail (运费试算)

interceptOrder (拦截订单)

getOrderFee (订单费用查询)

getBillingWeight (获取订单实际计费重)

getLastTrackCode(PDD专用-获取派送商信息)

getCargoTrackPdd(PDD专用-轨迹查询)

createFbaOrder (创建FBA订单)

batchGetDeliveryProof(批量获取发货证明)

getFbaLabel(批量获取FBA标签)

getWarehouseCode (获取仓库代码列表接口)

register(注册用户接口 -未公开)

customerLeads (客户线索接口-未公开)

华翰物流API文档

深圳市华翰鸿运国际物流技术有限公司

API接口文档V2.2

http code请求示例

```
POST /default/svc/web-service HTTP/1.1
Host: 127.0.0.1
Content-Type: application/xml
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callService>
      <paramsJson>{"codes":["GV436479377GB"]}</paramsJson>
      <appToken>123</appToken>
      <appKey>456</appKey>
      <service>getCargoTrack</service>
    </ns1:callService>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

PHP code 1请求示例

```
<?php
$curl = curl_init();

curl_setopt_array($curl, array(
  CURLOPT_URL => "http://127.0.0.1/default/svc/web-service",
  CURLOPT_RETURNTRANSFER => true,
  CURLOPT_ENCODING => "",
  CURLOPT_MAXREDIRS => 10,
  CURLOPT_TIMEOUT => 0,
  CURLOPT_FOLLOWLOCATION => true,
  CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
  CURLOPT_CUSTOMREQUEST => "POST",
  CURLOPT_POSTFIELDS => "<?xml version='1.0' encoding='utf-8'?>\r\n<SO
```

```

AP-ENV:Envelope xmlns:SOAP-ENV=\"http://schemas.xmlsoap.org/soap/envelope
/\\" xmlns:ns1=\"http://www.example.org/Ec/\"> \r\n  <SOAP-ENV:Body> \r\n
<ns1:callService> \r\n    <paramsJson>{\"codes\":[\"GV436479377GB\"]}</
paramsJson> \r\n    <appToken>123</appToken> \r\n    <appKey>456</a
ppKey> \r\n    <service>getCargoTrack</service> \r\n  </ns1:callServ
ice> \r\n  </SOAP-ENV:Body> \r\n</SOAP-ENV:Envelope>\r\n\",
CURLOPT_HTTPHEADER => array(
  \"Content-Type: application/xml\"
),
));

$response = curl_exec($curl);

curl_close($curl);
echo $response;
?>

```

PHP code 2 请求示例

```

<?php
$params = array(
    'codes' => array('GV436479377GB')
);
$req = array(
    'service' => 'getCargoTrack',
    'paramsJson' => json_encode($params),
    'appToken' => '123',
    'appKey' => '456'
);
$options = array (
    \"trace\" => true,
    \"connection_timeout\" => 1000,
    \"encoding\" => \"utf-8\"
);

$wsdl = 'http://127.0.0.1/default/svc/wsdl';

try {
    $client = new SoapClient ( $wsdl, $options );
    $result = $client->callService($req);
} catch (Exception $e) {
    echo $e->getMessage();
}
print_r($result);
?>

```

C# code 请求示例

```
var client = new RestClient("http://127.0.0.1/default/svc/web-service");
client.Timeout = -1;
var request = new RestRequest(Method.POST);
request.AddHeader("Content-Type", "application/xml");
request.AddParameter("application/xml", "<?xml version='1.0' encoding='utf-8'>\r\n<SOAP-ENV:Envelope xmlns:SOAP-ENV='http://schemas.xmlsoap.org/soap/envelope/' xmlns:ns1='http://www.example.org/Ec/'> \r\n<SOAP-ENV:Body> \r\n    <ns1:callService> \r\n        <paramsJson>{\"codes\": [\"GV436479377GB\"]}</paramsJson> \r\n        <appToken>123</appToken> \r\n        <appKey>456</appKey> \r\n        <service>getCargoTrack</service> \r\n    </ns1:callService> \r\n</SOAP-ENV:Body> \r\n</SOAP-ENV:Envelope>\r\n", ParameterType.RequestBody);
IRestResponse response = client.Execute(request);
Console.WriteLine(response.Content);
```

版本信息

版本信息

版本	修改日期	修改人	修改内容
1.0	2020/01/07	蔡兆锡	新建文档
1.1	2020/06/09	蔡兆锡	创建订单增加长宽高字段
1.2	2020/08/15	江杰军	更新部分字段描述
1.3	2020/09/03	蔡兆锡	新增批量打印标签
1.3	2020/09/03	江杰军	完善批量打印标签注解
1.4	2020/09/10	蔡兆锡	新增订单费用查询接口
1.5	2020/09/10	蔡兆锡	创建订单增加申报材质字段
1.6	2020/12/21	蔡兆锡	创建订单增加发件人税号字段
1.7	2021/1/15	蔡兆锡	申报明细增加申报材质和用途字段
1.8	2021/03/08	江杰军	增加显示轨迹状态代码说明
1.9	2021/06/18	蔡兆锡	新增字段欧盟税号
2.0	2022/05/31	江杰军	完善相关字段说明
2.1	2022/12/26	江杰军	增加PDD相关定制接口

公共请求参数

简要描述：

API公共请求参数说明

请求地址:

WebServices地址(如果用soap方法做对接，就用这个地址)

<http://api.hh-exp.com/default/svc/wsdl>

webApi地址(如果用curl方法做对接，就用这个地址，该地址支持postman请求)建议使用此模式

<http://api.hh-exp.com/default/svc/web-service>


注：此接口地址就是正式环境地址.

特别说明：不可以使用该接口域名进行客户端登陆操作(会出现无法登陆等异常)，此地址是专门给API接口使用！华翰客户端地址：http://www.hhddb.com 客户端应该使用此地址登陆操作！切记！！

请求公共参数:

参数名	类型	必填项	描述
appToken	String	√	API账号
appKey	String	√	API密码
service	String	√	接口方法，参考接口列表中service名称
paramsJson	String	√	请求的数据内容（json格式）， 参考接口列表中paramsJson示例说明

注：API账户密码是使用您在我司开户账号密码，登陆我司客户端：www.hhddb.com 生成对接的API账号密码 [步骤：登陆->API设置->添加]



请求XML:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callService>
      <paramsJson>{json}</paramsJson>
      <appToken>appToken</appToken>
      <appKey>appKey</appKey>
      <service>{service}</service>
    </ns1:callService>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

响应公共参数:

参数名	类型	必填项	描述
ask	String	√	响应标志，Success表示成功，Failure表示失败
message	String	√	消息提示
Error	Object		错误信息

Error格式:

参数名	类型	必填项	描述
errMessage	String	√	错误信息内容
errCode	String	√	错误码

pagination格式:

参数名	类型	必填项	描述
pageSize	String	√	分页大小
page	String	√	当前页

响应XML:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{json}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

备注:

如果JSON里面有"<"和"&",请转义成对应的XML实体。

createOrder (创建订单)

简要描述：

创建订单接口

service名称:

createOrder

paramsJson示例：

```
{
  "reference_no": "WWTEST202001084545",
  "shipping_method": "B测试产品",
  "country_code": "US",
  "order_weight": 1,
  "order_pieces": "1",
  "length":1,
  "width":1,
  "height":1,
  "Consignee": {
    "consignee_street": "19 N Long Ave",
    "consignee_street2": "",
    "consignee_name": "Xiao Cai",
    "consignee_telephone": "958465448",
    "consignee_postcode": "60644-3224",
    "consignee_province": "Illinois",
    "consignee_city": "Chicago",
    "consignee_taxno": "TA2020181245",
    "consignee_email": "9586645845@qq.com",
    "IOSS":"IM5280002079"
  },
  "Shipper": {
    "shipper_countrycode": "CN",
    "shipper_province": "GUANGDONG",
    "shipper_city": "SHENZHEN",
    "shipper_street": "pinghu 55 SHENZHEN GUANGDONG",
    "shipper_postcode": "518000",
    "shipper_name": "hh cai",
    "shipper_telephone": "9586458745",
  }
}
```

```
    "shipper_mobile": "18011911234",
    "shipper_taxno": "FAFA8181AA"
  },
  "ItemArr": [{
    "invoice_cnname": "手机外壳1",
    "invoice_enname": "Mobile phone shell1",
    "invoice_weight": 0.8,
    "invoice_quantity": "3",
    "invoice_unitcharge": 3.5,
    "sku": "4644392",
    "invoice_url": "http://www.aliexpress.com/item//4000599110017.htm
1"
  }, {
    "invoice_cnname": "手机外壳2",
    "invoice_enname": "Mobile phone shell2",
    "invoice_weight": 0.8,
    "invoice_quantity": "3",
    "invoice_unitcharge": 3.5,
    "sku": "4644392",
    "invoice_url": "http://www.aliexpress.com/item//4000599110017.htm
1"
  }
  ]
}
```

paramsJson参数:

参数名	数据类型	是否必填	说明
reference_no	string	Require	客户参考号(客户自定义单号，不能重复，需唯一)
shipping_method	string	Require	配送方式（产品代码） 可以通过“获取配送方式”接口获取列表， 也可以访问我司产品代码网站 http://www.hh-exp.cn/ProductCode/index.php 手工查询
country_code	string	Require	收件人国家二字码
extra_service	string	Option	附加服务代码， 每个以英文分号“;”隔开
order_weight	float	Require	订单重量，单位KG

参数名	数据类型	是否必填	说明
shipping_method_no	string	Option	服务商单号（追踪单号，默认不需要传值，由华翰接口返回）
order_pieces	int	Option	外包装件数，默认1（ 小包默认值1即可 ，发FBA空海运等一票货多箱的时候才需要根据情况设置）这个字段不是数量不要传错。
insurance_value	float	Option	投保金额，默认RMB
mail_cargo_type	string	Option	包裹申报种类（1-Gif礼品；2-CommercialSample商品货样；3-Document文件；4-Other其他。默认4）
length	float	Option	长，单位cm，默认1
width	float	Option	宽，单位cm，默认1
height	float	Option	高，单位cm，默认1

Consignee	Object	Require	收件人信息
Shipper	Object	Require	发件人信息
ItemArr	Object/Array	Require	海关申报信息

Consignee参数

参数名	数据类型	是否必填	说明
consignee_company	string	Option	收件人公司名
consignee_province	string	Option	收件人省
consignee_city	string	Option	收件人城市
consignee_street	string	Require	收件人地址1
consignee_street2	string	Option	收件人地址2
consignee_street3	string	Option	收件人地址3

consignee_street	string	Option	收件人地址
参数名	数据类型	是否必填	说明
consignee_postcode	string	Option	收件人邮编
consignee_name	string	Require	收件人姓名
consignee_telephone	string	Option	收件人电话
consignee_mobile	string	Option	收件人手机
consignee_email	string	Option	收件人邮箱
consignee_certificatetype	string	Option	证件类型（ID-身份证；PP-护照）
consignee_certificatecode	string	Option	证件号码

consignee_credentials_period	string	Option	证件有效期， 格式：2014-04-15
consignee_doorplate	string	Option	收件人门牌号（ 注意：除一些特殊专线产品要求单独上传门牌号外，门牌号直接放地址里面即可无需单独放到此字段 ）
consignee_taxno	string	Option	收件人税号（VAT税号）
IOSS	string	Option	欧盟税号（iOSS税号）

Shipper参数

参数名	数据类型	是否必填	说明
shipper_company	string	Option	发件人公司名
shipper_countrycode	string	Require	发件人国家二字码
shipper_province	string	Require	发件人省
shipper_city	string	Require	发件人城市
shipper_street	string	Require	发件人地址

参数名	数据类型	是否必填	发件人邮编说明
shipper_postcode	string	Require	发件人邮编
shipper_areacode	string	Option	区域代码
shipper_name	string	Require	发件人姓名
shipper_telephone	string	Require	发件人电话
shipper_mobile	string	Require	发件人手机
shipper_email	string	Option	发件人邮箱
shipper_fax	string	Option	发件人传真
order_note	string	Option	订单备注

shipper_taxno	string	Option	发件人税号（发件人VAT税号）
---------------	--------	--------	-----------------

ItemArr参数

参数名	数据类型	是否必填	说明
invoice_enname	string	Require	英文海关申报品名

invoice_cnname	string	Option	中文海关申报品名
invoice_weight	float	Require	申报重量，单位KG，精确到三位小数。
invoice_quantity	int	Require	数量
unit_code	string	Option	单位(MTR-米；PCE-件；SET-套)，默认PCE
invoice_unitcharge	float	Require	单价
invoice_currencycode	string	Option	申报币种，不传值默认为USD(美元)；USD-美元,AUD-澳元,CAD-加元,EUR-欧元,GBP-英镑,HKD-港币,MXN-墨西哥元,RMB-人民币,RUB-俄罗斯卢布,CNY-新加坡元

参数名	数据类型	是否必填	说明
hs_code	string	Option	俄罗斯卢布,SGD-新加坡元 海关协制编号(海关编码)
invoice_note	string	Option	配货信息
invoice_url	string	Option	产品销售地址（销售链接）
sku	string	Option	产品SKU编码
material	string	Option	申报材质
invoice_function	string	Option	用途

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Success","message":"Success","reference_no":"WWTEST202001084549","shipping_method_no":"LW423745051CN","order_code":"HHWEW0008000011YQ","track_status":"1","sender_info_status":"1","ODA":"","agent_number":"496409","time_cost(s)":"3.8042180538177"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Failure","message":"服务异常：订单数据不合法","reference_no":"WWTEST202001084545","Error":{"errMsg":"参考单号已存在[WWTEST202001084545]","errCode":"ORDER_REFER_ISEXISTS"},"time_cost(s)":"0.92805314064026"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
reference_no	string	客户单号
shipping_method_no	string	服务商单号(追踪单号\尾程派送单号)，如：RV507879168CN ,默认取此单号
order_code	string	华翰系统订单号，系统生成的唯一单号，如：HHWCO0296000051YQ，如果需要华翰运单号，可以获取这个字段，此单号也可以17TRACK或华翰官网（hh-exp.com）查询全程轨迹
track_status	string	track_status（1-已产生跟踪号，2-等待后续更新跟踪号,3-不需要跟踪号）——暂未启用此功能
sender_info_status	string	是否需要分配发件人地址（0-是，1-否）
ODA	string	是否需要ODA检验（Y-是）
agent_number	string	渠道换单号
Error	Object	参考公共请求参数中Error格式 (注意： 获取报错信息是 message +errMessage 才是完整的报错提示)

batchCreateOrder (批量创建订单)

简要描述：

批量创建订单接口

service名称:

batchCreateOrder

paramsJson示例：

```
[{
  "reference_no": "WWTEST202001084545",
  "shipping_method": "PK0032",
  "country_code": "US",
  "order_weight": 1,
  "order_pieces": "1",
  "length": 1,
  "width": 1,
  "height": 1,
  "Consignee": {
    "consignee_street": "19 N Long Ave",
    "consignee_street2": "",
    "consignee_name": "Xiao Cai",
    "consignee_telephone": "958465448",
    "consignee_postcode": "60644-3224",
    "consignee_province": "Illinois",
    "consignee_city": "Chicago",
    "consignee_taxno": "TA2020181245"
  },
  "Shipper": {
    "shipper_countrycode": "CN",
    "shipper_province": "GUANGDONG",
    "shipper_city": "SHENZHEN",
    "shipper_street": "pinghu 55 SHENZHEN GUANGDONG",
    "shipper_postcode": "518000",
    "shipper_name": "hh cai",
    "shipper_telephone": "18011911234",
    "shipper_mobile": "18011911234"
  }
},
```



```

    "ItemArr": [{
      "invoice_cnname": "手机壳1",
      "invoice_enname": "Mobile phone shell1",
      "invoice_weight": 1,
      "invoice_quantity": "1",
      "invoice_unitcharge": 3.3,
      "sku": "4644392"
    }, {
      "invoice_cnname": "手机壳2",
      "invoice_enname": "Mobile phone shell2",
      "invoice_weight": 1,
      "invoice_quantity": "1",
      "invoice_unitcharge": 3.3,
      "sku": "4644392"
    }
  ], {
    "shipper_hawbcode": "",
    "reference_no": "WWTEST202001084546",
    "shipping_method": "PK0032",
    "country_code": "US",
    "order_weight": 1,
    "order_pieces": "1",
    "length": 1,
    "width": 1,
    "height": 1,
    "Consignee": {
      "consignee_street": "19 N Long Ave",
      "consignee_street2": "",
      "consignee_name": "Xiao Cai",
      "consignee_telephone": "958465448",
      "consignee_postcode": "60644-3224",
      "consignee_province": "Illinois",
      "consignee_city": "Chicago",
      "consignee_taxno": "TA2020181246"
    },
    "Shipper": {
      "shipper_countrycode": "CN",
      "shipper_province": "GUANGDONG",
      "shipper_city": "SHENZHEN",
      "shipper_street": "pinghu 55 SHENZHEN GUANGDONG",
      "shipper_postcode": "518000",
      "shipper_name": "hh cai",
      "shipper_telephone": "18011911234",
      "shipper_mobile": "18011911234"
    },
    "ItemArr": [{

```

```
"invoice_cnname": "手机壳1",
"invoice_enname": "Mobile phone shell1",
"invoice_weight": 1,
"invoice_quantity": "1",
"invoice_unitcharge": 3.33,
"sku": "4644392"
},{
  "invoice_cnname": "手机壳2",
  "invoice_enname": "Mobile phone shell2",
  "invoice_weight": 1,
  "invoice_quantity": "1",
  "invoice_unitcharge": 3.33,
  "sku": "4644392"
}]
}]
```

paramsJson参数:

paramsJson参数参考createOrder

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>
        {
          "ask": "Success",
          "message": "Success",
          "Result": [
            {
              "ask": "Success",
              "message": "Success",
              "reference_no": "WWTEST202001084999",
              "shipping_method_no": "LW423680523CN",
              "order_code": "HHWEW0008000004YQ",
              "track_status": "1",
              "sender_info_status": "1",
              "ODA": "",
              "agent_number": "496494"
            }
          ]
        }
      </response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

```

    },
    {
      "ask": "Success",
      "message": "Success",
      "reference_no": "WWTEST202001084998",
      "shipping_method_no": "LW423680660CN",
      "order_code": "HHWEW0008000005YQ",
      "track_status": "1",
      "sender_info_status": "1",
      "ODA": "",
      "agent_number": "496514"
    }
  ],
  "Error": [],
  "time_cost(s)": "6.6593809127808"
}
</response>
</ns1:callServiceResponse>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

失败返回示例:

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>
        {
          "ask": "Success",
          "message": "Success",
          "Result": [
            {
              "ask": "Failure",
              "message": "服务异常：订单数据不合法",
              "reference_no": "WWTEST202001084999",
              "Error": {
                "errMessage": "参考单号已存在[WWTEST202001084999]",
                "errCode": "ORDER_REFER_ISEXISTS"
              }
            }
          ],
          {
            "ask": "Failure",
            "message": "服务异常：HHWEW0008000009YQ换号失

```

```
败。下家接口报错：异常:B03 收件人邮编不能为空";
    "reference_no": "WWTEST202001084997"
  }
],
  "Error": [],
  "time_cost(s)": "3.1871819496155"
}
</response>
</ns1:callServiceResponse>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
Result	string	参考 createOrder 的 response参数
Error	Object	参考公共请求参数中Error格式

getCargoTrack (轨迹查询)

简要描述：

轨迹查询接口

service名称:

getCargoTrack

paramsJson示例：

```
{
  "codes": [ "HHWDE9344000011YQ", "HHWDE9344000012YQ" ]
}
```

paramsJson参数:

参数名	数据类型	是否必填	说明
codes	Object/Array	Require	服务商单号shipping_method_no（或者系统订单号c 数组,如{"codes":["TFL1"," TFL2"]}

注：1、此单号为创建订单时候我司返回的追踪号（shipping_method_no 字段）

* 2、此接口支持批量查询，建议一次请求50票；不建议并发请求，并发可能会被防火墙拦截 *

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
```

```

<ns1:callServiceResponse>
  <response>{"ask":"Success","message":"Success","Data":[{"Code":"HHWDE9344000011YQ","Country_code":"FR","New_date":"2019-12-31 09:26:30","New_Comment":"快件操作完成","Status":"DF","Detail":[{"Occur_date":"2019-12-31 09:26:30","Status":"DF","Comment":"快件操作完成 Shipment departed from facility","track_area":"SHENZHEN"}, {"Occur_date":"2019-12-31 09:26:30","Status":"AF","Comment":"快件到达作业中心 Shipment arrived at facility","track_area":"SHENZHEN"}, {"Occur_date":"2019-12-10 17:33:00","Status":"IR","Comment":"快件电子信息已经收到 Shipment information received","track_area":""}]}], {"Code":"HHWDE9344000012YQ","Country_code":"FI","New_date":"2019-12-10 17:33:03","New_Comment":"运单电子信息已收到","Status":"NO","Detail":[{"Occur_date":"2019-12-10 17:33:03","Status":"IR","Comment":"快件电子信息已经收到 Shipment information received","track_area":""}]}], "Error":[], "time_cost(s)":"0.22901296615601"}</response>
</ns1:callServiceResponse>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

失败返回示例:

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Success","message":"Success","Data":[{"Code":"HHWDE9344000011KYQ","Country_code":"","New_date":"","New_Comment":"","Status":"","Detail":[]}, {"Code":"HHWDE9344000012kkYKQ","Country_code":"","New_date":"","New_Comment":"","Status":"","Detail":[]}], "Error":[], "time_cost(s)":"0.18701100349426"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Failure","message":"","Data":[], "Error":{"cnMessage":"单号不能为空","enMessage":"Order Code. can not be empty"},"time_cost(s)":"0.063003063201904"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```



response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
Data	Object	数据内容(2维数组)
Error	Object	参考公共请求参数中Error格式

Data参数:

参数名	数据类型	说明
Code	string	单号
Country_code	string	目的国家代码
New_date	string	最新的轨迹时间，格式为：YYYY-MM-DD HH:MM:SS
New_Comment	string	最新的轨迹内容
Status	string	轨迹状态码
Detail	Object	轨迹明细内容(2维数组)

Detail参数:

参数名	数据类型	说明
Occur_date	string	轨迹发生时间
Status	string	轨迹状态
Comment	string	轨迹内容
track_area	string	发生地点全称

轨迹状态代码对应表:

华翰系统状态码	华翰状态中文描述	华翰状态英文描述	17track状态码	17track子状态
IR	电子信息已收到	Shipment information received	收到信息	收到信息
AF	已入仓	Arrived at origin facility	运输途中	运输途中-揽收
DF	已出仓	Departed from origin facility	运输途中	运输途中-其它情况
GG	已过港	Transfer to Origin airport	运输途中	运输途中-其它情况
BG	已报关	Export customs clearance completed	运输途中	运输途中-其它情况
AP	已交航	Received by airport of Origin	运输途中	运输途中-其它情况
QF	已起飞	Departed from airport of Origin	运输途中	运输途中-离港
LD	已落地	Arrived at destination airport	运输途中	运输途中-到港
DR	到达目的地	Destination Reached	运输途中	运输途中-其它情况
QG	清关中	Import Customs clearance started	运输途中	运输途中-其它情况
YG	已清关	Import Customs clearance completed	运输途中	运输途中-其它情况
JY	已交邮	Has been given to local carrier	运输途中	运输途中-其它情况
CA	到达尾程承运商	arrived at last mile sorting center	运输途中	运输途中-其它情况
CB	离开尾程承运商	Leaving the terminal transfer center	运输途中	运输途中-其它情况
YQ	已提取	Arrived at sort facility	运输途中	运输途中-其它情况
IA	已上网	Internet Access	收到信息	运输途中-其它情况
WB	到达中转站	Arrived at Transit Facility	运输途中	运输途中-其它情况
WD	离开中转站	Departed from Transit Facility	运输途中	运输途中-其它情况
PB	到达待取	Arrival to be picked up	到达待取	运输途中-其它情况
ND	运输中	Normal delivery	运输途中	运输途中-其它情况
CC	派送妥投	Delivered	成功签收	成功签收
AC	清关异常	Abnormal customs clearance	可能异常	运输途中-需要资料
AE	清关失败	Customs clearance failed	可能异常	运输途中-其它情况
DS	已丢失	The package has been lost	可能异常	可能异常-丢失
FI	签收失败	Delivery failed	可能异常	可能异常-退件签收
UE	退件	Unread Expressage	可能异常	可能异常-退件中
UH	海外退件	Overseas return	可能异常	可能异常-退件签收

modifyOrderWeight （修改订单重量）

简要描述：

修改订单重量接口

service名称:

modifyOrderWeight

paramsJson示例：

```
[{
  "order_code": "HHWEW0007000006YQ",
  "weight": "0.02"
},{
  "order_code": "HHWEW0007000005YQ",
  "weight": "0.03"
}]
```

paramsJson参数:

参数名	数据类型	是否必填	说明
order_code	string	Require	客户单号（或者系统订单号，或者服务商单号都可以）
weight	string	Require	重量，单位KG,最多支持3位小数。

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
```

```
<response>{"ask": "Success", "message": "", "Result": [{"order_code": "HHWEW0007000004YQ", "ask": "Success", "message": "Success"}, {"order_code": "HHWEW0007000005YQ", "ask": "Success", "message": "Success"}], "time_cost(s)": "0.29701685905457"}</response>
</ns1:callServiceResponse>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask": "Success", "message": "", "Result": [{"order_code": "HHWEW0007000006YQ", "ask": "Failure", "Error": {"errMsg": "只支持“草稿”，“换号中”，“已预报”等状态更新重量!", "errCode": ""}}, {"order_code": "HHWEW000700000KYQ", "ask": "Failure", "Error": {"errMsg": "单号不存在!", "errCode": ""}}], "time_cost(s)": "0.25001502037048"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
Result	string	结果数组
Error	Object	参考公共请求参数中Error格式

Result参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数

modifyOrderWeight (修改订单重量)

参数名	数据类型	说明
message	string	参考公共请求参数中response参数
order_code	string	请求单号
Error	Object	参考公共请求参数中Error格式

getTrackNumber (查询跟踪号)

简要描述：

查询运单入库后实际发货跟踪号接口

service名称:

getTrackNumber

paramsJson示例：

```
{
  "reference_no": [ "HHWEW0007000008YQ", "HHWEW0007000009YQ" ]
}
```

paramsJson参数:

参数名	数据类型	是否必填	说明
reference_no	Object	Require	客户单号reference_no（或者系统运单号order_co 数组,如{" reference_no ":["code1"," code2"]}

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask": "Success", "data": [{"state": "1", "OrderNumber": "WWW3THHF5S25A23", "TrackingNumber": "L0715818719CN", "WayBillNumber": "HHWEW0007000008YQ"}, {"state": "1", "OrderNumber": "WWW3THHF5S25A23", "TrackingNumber": "L0715818719CN", "WayBillNumber": "HHWEW0007000008YQ"}], "Error": [], "message": "全部获取成功", "time_cost(s)": "0.35601997375488"}</response>
```

```
</ns1:callServiceResponse>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Failure","data":[{"state":"0","OrderNumber":"HHWEW0007000008YQK","TrackingNumber":"","WayBillNumber":"","msg":"单号:[HHWEW0007000008YQK]订单信息不存在"}, {"state":"0","OrderNumber":"HHWEW0007000008YQL","TrackingNumber":"","WayBillNumber":"","msg":"单号:[HHWEW0007000008YQL]订单信息不存在"}],"Error":[],"message":"全部获取失败","time_cost(s)":"0.24401378631592"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
data	Object	数据内容(2维数组)
Error	Object	参考公共请求参数中Error格式

data参数:

参数名	数据类型	说明
state	int	1为成功; 0为失败
OrderNumber	string	客户单号
TrackingNumber	string	跟踪号

getTrackNumber (查询跟踪号)

参数名	数据类型	说明
WayBillNumber	string	系统运单号
msg	string	错误信息

getShippingMethod （获取配送方式）

简要描述：

获取配送方式接口

service名称:

getShippingMethod

paramsJson示例：

paramsJson不需要传参

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Success","data":[{"code":"PK0032","cn_name":"B测试产品","en_name":"B测试产品","group_code":"SP","track_status":"N","aging":"1-3","note":""},{ "code":"PK0048","cn_name":"C测试产品","en_name":"Cproduct","group_code":"SP","track_status":"N","aging":"1-2","note":""},{ "code":"PK0059","cn_name":"D测试产品","en_name":"Dproduct","group_code":"MA","track_status":"N","aging":"","note":""},{ "code":"FEDEX-IE","cn_name":"FEDEX-IE","en_name":"FEDEX-IE","group_code":"FE","track_status":"Y","aging":"1-7","note":"FEDEX-IE"},{ "code":"FEDEX-IP","cn_name":"FEDEX-IP","en_name":"FEDEX-IP","group_code":"FE","track_status":"Y","aging":"1-7","note":""},{ "code":"HKUPSDLCX","cn_name":"HK-UPS代理促销","en_name":"HKUPSDLCX","group_code":"UP","track_status":"N","aging":"","note":""},{ "code":"HKUPSTH5","cn_name":"HK-UPS特惠5000","en_name":"HKUPSTH5","group_code":"UP","track_status":"Y","aging":"","note":""},{ "code":"HKUPSTH","cn_name":"HK-UPS特惠6000","en_name":"HKUPSTH6000","group_code":"UP","track_status":"Y","aging":"","note":""},{ "code":"HKUPSTHCX","cn_name":"HK-UPS特惠促销","en_name":"HKUPSTHCX","group_code":"UP","track_status":"Y","aging":"","note":""},{ "code":"HKUPSLDF","cn_name":"HK-UPS蓝单F","en_name":"HKUPSLDF","group_code":"UP","track_status":"Y","aging":"","note":""},{ "code":"HKUPSLDCX","c
```

```

n_name":"HK-UPS蓝单促销","en_name":"HKUPSLDCX","group_code":"UP","track_status":"Y","aging":"","note":""},{
"code":"HKUPSKS","cn_name":"HK-UPS速快","en_name":"HKUPSKS","group_code":"SP","track_status":"Y","aging":"","note":""},
{"code":"HKDHLDLJ","cn_name":"HKDHL-代理价","en_name":"HKDHLDLJ","group_code":"DH","track_status":"Y","aging":"1-7","note":""},
{"code":"HLDHLMGJ","cn_name":"HKDHL-敏感价","en_name":"HKDHLMGJ","group_code":"DH","track_status":"Y","aging":"1-7","note":""},
{"code":"HKUPSDLJ","cn_name":"HKUPS-代理价","en_name":"HKUPSDLJ","group_code":"UP","track_status":"Y","aging":"1-7","note":""},
{"code":"HKUPSTH5F","cn_name":"HKUPS特惠5000-F","en_name":"HKUPSTH5F","group_code":"UP","track_status":"Y","aging":"","note":""},
{"code":"PK0028","cn_name":"UPS红单包税","en_name":"UPSHDBSCP","group_code":"SP","track_status":"N","aging":"","note":""},
{"code":"PK0019","cn_name":"US--速快(平衡车类)","en_name":"USSKPHCCP","group_code":"SP","track_status":"N","aging":"","note":""},
{"code":"PK0018","cn_name":"US--速快(敏感)","en_name":"USSKMGCP","group_code":"SP","track_status":"N","aging":"","note":""},
{"code":"PK0014","cn_name":"US--速快(纯电)","en_name":"USSKCDP","group_code":"SP","track_status":"Y","aging":"","note":""},
{"code":"PK0015","cn_name":"US--速快(美国东部)","en_name":"USSKMGBSCP","group_code":"SP","track_status":"Y","aging":"","note":""},
{"code":"PK0017","cn_name":"US--速快(美国中部)","en_name":"USSKMGZSCP","group_code":"SP","track_status":"N","aging":"","note":""},
{"code":"PK0016","cn_name":"US--速快(美国西部)","en_name":"USSKMGXSCP","group_code":"SP","track_status":"Y","aging":"","note":""},
{"code":"EST","cn_name":"俄速通","en_name":"EST","group_code":"MA","track_status":"Y","aging":"1-30","note":""},
{"code":"NJGH","cn_name":"南京挂号","en_name":"NJGH","group_code":"MA","track_status":"Y","aging":"1-30","note":""},
{"code":"XMPYCP","cn_name":"厦门平邮","en_name":"XMPYCP","group_code":"PY","track_status":"N","aging":"1-30","note":""},
{"code":"PK0053","cn_name":"小包测试","en_name":"小包测试","group_code":"SP","track_status":"Y","aging":"1-3","note":""},
{"code":"DHLXB","cn_name":"德国DHL专线","en_name":"DGDHLZX","group_code":"SP","track_status":"Y","aging":"1-15","note":""},
{"code":"PK0095","cn_name":"德国专线","en_name":"DGZXC","group_code":"SP","track_status":"Y","aging":"3-7","note":""},
{"code":"PK0013","cn_name":"日本FBA专线(平衡车类)","en_name":"RBFBAZXPCLCP","group_code":"SP","track_status":"N","aging":"","note":"RBFBAZXPCLCP"},
{"code":"PK0011","cn_name":"日本FBA专线(深圳直航普货)","en_name":"RBFBAZXSZZHPHCP","group_code":"SP","track_status":"N","aging":"","note":""},
{"code":"PK0012","cn_name":"日本FBA专线(深圳直航经济)","en_name":"RBFBAZXSZZHJJ","group_code":"SP","track_status":"N","aging":"","note":""},
{"code":"PK0010","cn_name":"日本FBA专线(香港直航)","en_name":"RBFBAZXGZH","group_code":"SP","track_status":"N","aging":"","note":""},
{"code":"PK0047","cn_name":"欧洲FBA空运(单)","en_name":"OZFAKYD","group_code":"SP","track_status":"N","aging":"","note":"欧洲FBA空运(单)"},
{"code":"PK0051","cn_name":"欧洲FBA空运(卡板)","en_name":"OZFAKYKB","group_code":"SP","track_status":"N","aging":"","note":""},
{"code":"PK0044","cn_name":"欧洲FBA空运(大)","en_name":"OZFAKYDCP","group_code":"SP","track_status":"Y","aging":"1-10","note":""},
{"code":"PK0057","cn_name":"泰邮平邮测试","en_name":"TYPYCSC","group_code":"SP",

```



```

"track_status":"N","aging":"","note":""},{ "code":"PK0050","cn_name":"测试A
PI换号","en_name":"API测试","group_code":"PY","track_status":"N","aging":
":"","note":""},{ "code":"PK0058","cn_name":"测试hh","en_name":"testhh","grou
p_code":"PY","track_status":"N","aging":"","note":""},{ "code":"PK0049","c
n_name":"测试强制换号","en_name":"强制换号","group_code":"SP","track_statu
s":"N","aging":"","note":""},{ "code":"PK0007","cn_name":"测试海运(方)","en
_name":"测试海运(方)","group_code":"MA","track_status":"Y","aging":" 3- 3
0","note":""},{ "code":"HYOZFBA","cn_name":"海运-欧洲FBA","en_name":"HYOZFB
A","group_code":"SP","track_status":"Y","aging":"","note":""},{ "code":"PK
0052","cn_name":"海运DEMO","en_name":"HHHYDEMO","group_code":"SP","track_s
tatus":"Y","aging":"2-3","note":""},{ "code":"SZDHLAJ","cn_name":"深圳DHL-A
价","en_name":"SZDHLAJ","group_code":"DH","track_status":"Y","aging":"","
note":""},{ "code":"SZDHLXHJ","cn_name":"深圳DHL小货价","en_name":"SZDHLXH
J","group_code":"DH","track_status":"Y","aging":"1-7","note":""},{ "code":
"SZEMS","cn_name":"深圳EMS","en_name":"SZEMS","group_code":"EM","track_sta
tus":"Y","aging":"1-7","note":""},{ "code":"EUB-SZ","cn_name":"深圳eub","en
_name":"SZEUB","group_code":"EM","track_status":"Y","aging":"1-15","note"
:""},{ "code":"SZPYCP","cn_name":"深圳平邮","en_name":"SZPYCP","group_code"
:"PY","track_status":"Y","aging":"3-30","note":""},{ "code":"PK0041","cn_n
ame":"深圳平邮(俄罗斯)","en_name":"SZPYRUCP","group_code":"PY","track_stat
us":"N","aging":"1-30","note":""},{ "code":"PK0043","cn_name":"深圳平邮-带
电","en_name":"SZPYDDCP","group_code":"PY","track_status":"N","aging":"1-
30","note":""},{ "code":"PK0001","cn_name":"深圳挂号","en_name":"SZGH","gro
up_code":"MA","track_status":"Y","aging":"1-30","note":""},{ "code":"PK004
0","cn_name":"深圳挂号(俄罗斯)","en_name":"SZGHRUCP","group_code":"MA","tr
ack_status":"Y","aging":"1-30","note":"只到俄罗斯"},{ "code":"PK0042","cn_n
ame":"深圳挂号-带电","en_name":"SZGHDDCP","group_code":"MA","track_status"
:"Y","aging":"1-30","note":""},{ "code":"XSXMPYCP","cn_name":"线上-厦门平
邮","en_name":"XSXMPYCP","group_code":"PY","track_status":"Y","aging":"1-
30","note":""},{ "code":"XSZZPY","cn_name":"线上-郑州平邮","en_name":"XSZZP
Y","group_code":"MA","track_status":"Y","aging":"1-15","note":""},{ "code"
:"XSZZGH","cn_name":"线上-郑州挂号","en_name":"XSZZGH","group_code":"MA",
"track_status":"Y","aging":"1-15","note":""},{ "code":"PK0029","cn_name":
"美国FBA海运散货","en_name":"MGFBAHYSHCPC","group_code":"SP","track_statu
s":"N","aging":"","note":""},{ "code":"PK0023","cn_name":"美国UPS专线(东
部)","en_name":"MGUPSZXDBCP","group_code":"SP","track_status":"N","aging"
:"","note":""},{ "code":"PK0025","cn_name":"美国UPS专线(中部)","en_name":"M
GUPSZXZBCP","group_code":"SP","track_status":"N","aging":"","note":""},{
"code":"PK0024","cn_name":"美国UPS专线(西部)","en_name":"MGUPSZXHBCP","gro
up_code":"SP","track_status":"N","aging":"","note":""},{ "code":"HEB","cn_
name":"翰俄宝","en_name":"HEB","group_code":"MA","track_status":"Y","agin
g":"1-30","note":""},{ "code":"PK0056","cn_name":"航空小包测试","en_name":
"HHXBCS","group_code":"PY","track_status":"N","aging":"","note":""},{ "cod
e":"PK0030","cn_name":"英国FBA海运散货(不含税)","en_name":"YGFBAHYSHCP","g
roup_code":"SP","track_status":"N","aging":"","note":""},{ "code":"YGZXCP"
,"cn_name":"英国专线","en_name":"YGZXCP","group_code":"SP","track_status":

```

```
"Y","aging":"1-7","note":""},{ "code":"HLPY","cn_name":"荷兰平邮","en_name":"HLPY","group_code":"PY","track_status":"Y","aging":"1-30","note":""},{ "code":"HLGH","cn_name":"荷兰挂号","en_name":"HLGH","group_code":"MA","track_status":"Y","aging":"1-20","note":""},{ "code":"ZZPY","cn_name":"郑州平邮","en_name":"ZZPY","group_code":"PY","track_status":"N","aging":"1-30","note":""},{ "code":"ZZGH","cn_name":"郑州挂号","en_name":"ZZGH","group_code":"MA","track_status":"Y","aging":"1-30","note":""}], "time_cost(s)": "1.5290870666504"}</response>
</ns1:callServiceResponse>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
data	Object	数据内容(2维数组)
Error	Object	参考公共请求参数中Error格式

data参数:

参数名	数据类型	说明
code	string	运输方式代码
cn_name	string	中文名称
en_name	string	英文名称
group_code	string	产品组
track_status	string	是否可跟踪(TRACK)，N为不可跟踪、Y为可跟踪
aging	string	派送时效
note	string	备注

getLabelUrl (获取标签)

简要描述：

获取标签接口

service名称:

getLabelUrl

paramsJson示例：

```
{
  "reference_no": "HHWEW0006000012YQ",
  "label_type": 1,
  "label_content_type": 4
}
```

paramsJson参数:

参数名	数据类型	是否必填	说明
reference_no	string	Require	客户单号reference_no（或者系统运单号order_code，或服务商单号shipping_method_no都可以）
label_type	int	Require	PDF标签尺寸类型（1：10 * 10标签；2：A4纸；3：10 * 15标签）
label_content_type	int	option	1-标签；2-报关单；3-配货单；4-标签+报关单；5-标签+配货单；6-标签+报关单+配货单，默认为4

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask": "Success", "message": "获取标签成功", "Error": [], "type": "pdf", "url": "http://127.0.0.1/index/get-label/code/HHWEW0006000012YQ", "time_cost(s)": "0.88304996490479"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask": "Failure", "message": "", "Error": {"errCode": "", "errMessage": "HHWEW0006000012KYQ订单不存在"}, "type": "pdf", "url": "", "time_cost(s)": "0.18701100349426"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
url	string	PDF标签格式URL地址。注标签URL有效时间为1个星期，如果未保存标签文件到本地，可以重新调用获取标签接口生成新的标签。
type	string	文件格式
Error	Object	参考公共请求参数中Error格式

batchGetLabelUrl (批量获取标签)

简要描述：

批量获取标签接口

注：暂时批量获取标签的接口只能打印同一物流产品的订单，不同物流产品混合打印会报错

service名称:

batchGetLabelUrl

paramsJson示例：

```
{
  "reference_nos":["HHWEW0191000054YQ","HHWEW0191000046YQ"],
  "label_type":1,
  "label_content_type":6,
  "extra_option":{
    "print_declare_info":"N"
  }
}
```

paramsJson参数:

参数名	数据类型	是否必填	说明
reference_nos	object	Require	客户参考号（或者系统运单号order_code 或服务商追踪号shipping_method_no ） 注意：一次性最多支持20票批量生成,超过数量容易出现获取失败或超时等错误
label_type	int	Require	PDF标签尺寸类型：1：10 * 10 标签；2：A4纸；3：10 * 15标签
			1-标签；2-报关单；3-配货单；4-标签

label_content_type 参数名	int 数据类型	Option 是否必填	+报关单；5-标签+配货单；6-标签 说明 +报关单+配货单，默认为4
extra_option	object	Option	标签可选项

extra_option参数:

参数名	数据类型	是否必填	说明
print_declare_info	string	Option	是否打印配货信息：Y是，N否，默认为Y

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Success","message":"Success","url":"http://192.168.16.21:10001/PDF/aa74bb0c-d7db-4182-9831-d9ce1f39f828.pdf","time_cost(s)": "7.1494090557098"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Failure","message":"","Error":{"errCode":"","errMessage":"HHWEW0191000054YYQ订单不存在"},"time_cost(s)": "0.29101586341858"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
url	string	PDF标签格式URL地址
Error	Object	参考公共请求参数中Error格式

cancelOrder （取消订单）

简要描述：

取消订单接口

service名称:

cancelOrder

paramsJson示例：

```
{
  "reference_no": "HHWEW0007000006YQ"
}
```

paramsJson参数:

参数名	数据类型	是否必填	说明
reference_no	string	Require	客户单号（或者系统运单号），注：只有草稿、已预报状态支持取消。

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Success","message":"Success","reference_no":"HHWEW0007000005YQ","time_cost(s)":"0.45802593231201"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```


失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Failure","message":"订单不存在","reference_no":"HHWEW00070000006KYQ","Error":{"errMessage":"订单不存在","errCode":"5000"},"time_cost(s)":"0.2200129032135"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
reference_no	string	需要删除的客户单号（或者系统运单号）
Error	Object	参考公共请求参数中Error格式

getOrder (查询订单)

简要描述：

查询订单接口

service名称:

getOrder

paramsJson示例：

```
{
  "reference_no": "HHWEW0007000006YQ"
}
```

paramsJson参数:

参数名	数据类型	是否必填	说明
reference_no	string	Require	客户参考号（或者系统运单号）

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask": "Success", "message": "Success", "reference_no": "HHWEW0007000006YQ", "data": {"shipping_method": "PK0032", "country_code": "ES", "reference_no": "WWW3THHF5S25A13D416", "shipper_hawbcode": "HHWEW0007000006YQ", "shipping_method_no": "L0715812132CND664", "order_weight": "0.000", "order_pieces": "1", "buyer_id": "", "modify_date": "2020-01-08 15:03:27", "mail_cargo_type": "4", "insurance_value": "0.000", "Consignee": {"consignee_countrycode": "ES", "consignee_company": "", "consignee_province": "aa", "consignee_nam
```

```
e":"sdg","consignee_city":"dfh","consignee_telephone":"1212521","consigne
e_mobile":"","consignee_postcode":"","consignee_email":"","consignee_stre
et":"SDAGSDGSDG","consignee_street2":"","consignee_street3":"","consignee
_certificatetype":"","consignee_certificatecode":"","consignee_credential
s_period":"","consignee_doorplate":"","consignee_taxno":"AABBCC008"},"Shi
pper":{"shipper_name":"hh cai","shipper_company":"","shipper_countrycode"
:"CN","shipper_province":"GUANGDONG","shipper_city":"SHENZHEN","shipper_s
treet":"pinghu 55 SHENZHEN GUANGDONG","shipper_postcode":"518000","shippe
r_areacode":"","shipper_telephone":"18011911234","shipper_mobile":"180119
11234","shipper_email":"","shipper_fax":""},"ItemArr":[{"invoice_cnname":
"手机壳","invoice_enname":"sd","unit_code":"PCE","invoice_weight":"1.000",
"invoice_quantity":"1","invoice_totalcharge":"3.33","invoice_totalWeight"
:"1.000","invoice_currencycode":"USD","hs_code":"","invoice_note":"","inv
oice_url":"","sku":"4644392","sku_audit_status":"","CertificateRemark":"","
HSTaxrate":"0.00000","type_code":"","box_no":"U001","Material":"","ASI
N":"","invoice_function":"","invoice_brand":"","invoice_unitcharge":"3.3
3"}]]},"time_cost(s)":"0.27301597595215"}</response>
</ns1:callServiceResponse>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelo
pe/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Failure","message":"订单不存在","reference_n
o":"HHWEW0007000006YKQ","time_cost(s)":"0.22101211547852"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
reference_no	string	客户单号
data	string	数据内容(二维数组)

data	string	数据内容(二维数组)
参数名	数据类型	说明
err_code	Object	参考公共请求参数中Error格式

data参数:

参数名	数据类型	说明
shipping_method	string	配送方式
country_code	string	收件人国家二字码
reference_no	string	客户参考号
shipper_hawbcode	string	运单号
shipping_method_no	string	服务商单号
order_weight	float	订单重量, 单位KG, 默认为0.2
order_pieces	int	外包装件数,默认1
buyer_id	string	买家ID
modify_date	string	修改时间
mail_cargo_type	string	包裹申报种类（1-Gif礼品； 2-CommercialSample商品货样； 3-Document文件； 4-Other其他），默认4
insurance_value	float	投保金额,币种USD
Consignee	Object	收件人信息
Shipper	Object	发件人信息
ItemArr	Object/Array	海关申报信息

Consignee参数:

参数名	数据类型	说明
consignee_countrycode	string	收件人国家二字码
consignee_company	string	收件人公司名
consignee_province	string	收件人省

参数名	数据类型	说明
consignee_name	string	收件人姓名
consignee_city	string	收件人城市
consignee_telephone	string	收件人电话
consignee_mobile	string	收件人手机
consignee_postcode	string	收件人邮编
consignee_email	string	收件人邮箱

consignee_street	string	收件人地址1
consignee_street2	string	收件人地址2
consignee_street3	string	收件人地址3
consignee_certificatetype	string	证件类型 ID:身份证 PP:护照
consignee_certificatecode	string	证件号码
consignee_credentials_period	string	有效期,格式: 2014-04-15
consignee_doorplate	string	收件人名牌号
consignee_taxno	string	收件人税号

Shipper参数:

参数名	数据类型	说明
shipper_name	string	发件人姓名
shipper_company	string	发件人公司名
shipper_countrycode	string	发件人国家二字码
shipper_province	string	发件人省
shipper_city	string	发件人城市
shipper_street	string	发件人地址

参数名	数据类型	说明
shipper_postcode	string	发件人邮编
shipper_areacode	string	区域代码
shipper_telephone	string	发件人电话
shipper_mobile	string	发件人手机
shipper_email	string	发件人邮箱
shipper_fax	string	发件人传真

ItemArr参数:

参数名	数据类型	说明
invoice_cnname	string	中文海关申报品名
invoice_enname	string	海关申报品名
unit_code	string	单位(MTR(米), PCE(件), SET(套)), 默认PCE
invoice_weight	float	申报重量, 单位KG, 精确到三位小数。
invoice_quantity	int	数量
invoice_totalcharge	float	总价
invoice_totalWeight	float	总重量
invoice_currencycode	string	申报币种, 默认为USD(美元)
hs_code	string	海关协制编号
invoice_note	string	配货信息
invoice_url	string	销售地址
sku	string	产品SKU编码
invoice_unitcharge	float	单价

feeTrail (运费试算)

简要描述：

运费试算接口

service名称:

feeTrail

paramsJson示例：

```
{
  "country_code": "US",
  "weight": "1",
  "length": "1",
  "width": "1",
  "height": "1"
}
```

paramsJson参数:

参数名	数据类型	是否必填	说明
country_code	string	Require	国家二字码
weight	float	Require	订单重量(KG)
length	float	Option	包裹长(CM)
width	float	Option	包裹宽(CM)
height	float	Option	包裹高(CM)

response XML示例:

成功返回示例:

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Success","message":"Success","data":[{"ChargeWeight":"1.000","Effectiveness":"3-7","FreightCostFee":"","FreightFee":"117.22","FuelFee":"21.39","InsuranceFee":"0.00","OtherFee":"1.00","Pr_id":"11983","ProductSort":"3","RegisteredFee":"0.00","Remark":"1、报价不含油不含税、海关罚款、仓储费以及收件人责任所引起的退件费等；2、偏远地区的快件需加收偏远地区附加费，标准为4.6港币/KG，最低收费为230港币/每票,偏远地区附加费须另加燃油附加费；3、高风险地区附加费:200HKD/票（需加燃油，文件和包裹都适用，具体涉及国家请查看报价表）。","ServiceCnName":"HKDHL-代理价","ServiceCode":"HKDHLDLJ","ServiceEnName":"HKDHLDLJ","TotalFee":"139.61","Traceability":"Y","VolumeCharge":"5000","m_ServiceCode":"HKDHLDLJ"}, {"ChargeWeight":"1.000","Effectiveness":"3-7","FreightCostFee":"","FreightFee":"118.32","FuelFee":"21.59","InsuranceFee":"0.00","OtherFee":"1.00","Pr_id":"11984","ProductSort":"3","RegisteredFee":"0.00","Remark":"","ServiceCnName":"HKDHL-敏感价","ServiceCode":"HLDHLMGJ","ServiceEnName":"HKDHLMGJ","TotalFee":"140.91","Traceability":"Y","VolumeCharge":"5000","m_ServiceCode":"HLDHLMGJ"}, {"ChargeWeight":"1.000","Effectiveness":"3-7","FreightCostFee":"","FreightFee":"107.15","FuelFee":"19.55","InsuranceFee":"0.00","OtherFee":"0.00","Pr_id":"3050","ProductSort":"2","RegisteredFee":"0.00","Remark":"1、报价不含油不含税；2、偏远地区是否请自行先查询，我司不代为查询。目的地去往偏远地区的快件需加收偏远地区附加费，标准为RMB3.2/KG，每票最低收费为RMB180/票（文件特惠价请看当面表格说明）偏远地区附加费须另行收取燃油附加费，发货后6个月内有效，官网能查询到偏远地区我司不提供DHL账单。","ServiceCnName":"深圳DHL小货价","ServiceCode":"SZDHLXHJ","ServiceEnName":"SZDHLXHJ","TotalFee":"126.7","Traceability":"Y","VolumeCharge":"5000","m_ServiceCode":"SZDHLXHJ"}, {"ChargeWeight":"1.0","Effectiveness":"7-20","FreightCostFee":"","FreightFee":"63.25","FuelFee":"0.00","InsuranceFee":"0.00","OtherFee":"0.00","Pr_id":"11647","ProductSort":"1","RegisteredFee":"0.00","Remark":"1、该渠道可以接固体化妆品，乳膏状化妆品，磁性支架，蓝牙耳机，不带烟油电子烟，泡沫盒（较重）；2、部分国家可接内置电池及少量配套电池，系统需要分开下单，分开包装，分开交货（详细查看报价表）；3、面单要求：10CM*10CM,面单要干净整洁，条码精度要大于300DPI，须用自粘型热敏纸张打印面单。","ServiceCnName":"深圳平邮","ServiceCode":"SZPYCP","ServiceEnName":"SZPYCP","TotalFee":"63.25","Traceability":"Y","VolumeCharge":"","m_ServiceCode":"SZPYCP"}, {"ChargeWeight":"1.0","Effectiveness":"7-20","FreightCostFee":"","FreightFee":"63.25","FuelFee":"0.00","InsuranceFee":"0.00","OtherFee":"0.00","Pr_id":"11649","ProductSort":"1","RegisteredFee":"0.00","Remark":"1、该渠道可以接固体化妆品，乳膏状化妆品，磁性支架，蓝牙耳机，不带烟油电子烟，泡沫盒（较重）；2、部分国家可接内置电池及少量配套电池，系统需要分开下单，分开包装，分开交货（详细查看报价表）；3、面单要求：10CM*10CM,面单要干净整洁，条码精度要大于300DPI，须用自粘型热敏纸张打印面单。","ServiceCnName":"深圳平邮(内置电)","ServiceCode":"PK0043","ServiceEnName":"SZPYDDCP","TotalFee":

```



```

: "63.25", "Traceability": "Y", "VolumeCharge": "", "m_ServiceCode": "PK0043"}, {
"ChargeWeight": "1.0", "Effectiveness": "7-20", "FreightCostFee": "", "FreightFee": "53.00", "FuelFee": "0.00", "InsuranceFee": "0.00", "OtherFee": "0.00", "Pr_id": "11639", "ProductSort": "1", "RegisteredFee": "20.00", "Remark": "1、带电货物需分开下单，分开交货2、本渠道适用于带内置电池产品，包括手机、平板电脑、笔记本电脑、数码相机、电子表、蓝牙键盘、多功能闹钟、无线路由器、电子烟（不含烟油等液体）等内置锂电池产品；3、面单要求：10CM*10CM,面单要干净整洁，条码精度要大于300DPI，须用自粘型热敏纸张打印面单。", "ServiceCnName": "深圳挂号", "ServiceCode": "PK0001", "ServiceEnName": "SZGH", "TotalFee": "73", "Traceability": "Y", "VolumeCharge": "", "m_ServiceCode": "PK0001"}, {"ChargeWeight": "1.0", "Effectiveness": "7-20", "FreightCostFee": "", "FreightFee": "53.00", "FuelFee": "0.00", "InsuranceFee": "0.00", "OtherFee": "0.00", "Pr_id": "11641", "ProductSort": "1", "RegisteredFee": "20.00", "Remark": "1、带电货物需分开下单，分开交货2、本渠道适用于带内置电池产品，包括手机、平板电脑、笔记本电脑、数码相机、电子表、蓝牙键盘、多功能闹钟、无线路由器、电子烟（不含烟油等液体）等内置锂电池产品；3、面单要求：10CM*10CM,面单要干净整洁，条码精度要大于300DPI，须用自粘型热敏纸张打印面单。", "ServiceCnName": "深圳挂号(内置电)", "ServiceCode": "PK0042", "ServiceEnName": "SZGHDDCP", "TotalFee": "73", "Traceability": "Y", "VolumeCharge": "", "m_ServiceCode": "PK0042"}, {"ChargeWeight": "1.0", "Effectiveness": "", "FreightCostFee": "", "FreightFee": "63.25", "FuelFee": "0.00", "InsuranceFee": "0.00", "OtherFee": "0.00", "Pr_id": "11675", "ProductSort": "0", "RegisteredFee": "0.00", "Remark": "", "ServiceCnName": "湖南平邮", "ServiceCode": "PK0247", "ServiceEnName": "HNPPYC", "TotalFee": "63.25", "Traceability": "N", "VolumeCharge": "", "m_ServiceCode": "PK0247"}, {"ChargeWeight": "1.0", "Effectiveness": "7-20", "FreightCostFee": "", "FreightFee": "63.25", "FuelFee": "0.00", "InsuranceFee": "0.00", "OtherFee": "0.00", "Pr_id": "11652", "ProductSort": "0", "RegisteredFee": "0.00", "Remark": "1、该渠道可以接固体化妆品，乳膏状化妆品，磁性支架，蓝牙耳机，不带烟油电子烟，泡沫盒（较重）；2、部分国家可接内置电池及少量配套电池，系统需要分开下单，分开包装，分开交货（详细查看报价表）；3、面单要求：10CM*10CM,面单要干净整洁，条码精度要大于300DPI，须用自粘型热敏纸张打印面单。", "ServiceCnName": "深圳平邮(纽扣电)", "ServiceCode": "PK0078", "ServiceEnName": "SZPYNKD", "TotalFee": "63.25", "Traceability": "Y", "VolumeCharge": "", "m_ServiceCode": "PK0078"}, {"ChargeWeight": "1.0", "Effectiveness": "7-20", "FreightCostFee": "", "FreightFee": "63.25", "FuelFee": "0.00", "InsuranceFee": "0.00", "OtherFee": "0.00", "Pr_id": "10906", "ProductSort": "0", "RegisteredFee": "0.00", "Remark": "1、该渠道可以接固体化妆品，乳膏状化妆品，磁性支架，蓝牙耳机，不带烟油电子烟，泡沫盒（较重）；2、部分国家可接内置电池及少量配套电池，系统需要分开下单，分开包装，分开交货（详细查看报价表）；3、面单要求：10CM*10CM,面单要干净整洁，条码精度要大于300DPI，须用自粘型热敏纸张打印面单。", "ServiceCnName": "线上-深圳平邮(WISH)", "ServiceCode": "XSSZPYCP", "ServiceEnName": "XSSZPYCP", "TotalFee": "63.25", "Traceability": "Y", "VolumeCharge": "", "m_ServiceCode": "XSSZPYCP"}, {"ChargeWeight": "1.0", "Effectiveness": "3-25", "FreightCostFee": "", "FreightFee": "63.25", "FuelFee": "0.00", "InsuranceFee": "0.00", "OtherFee": "1.00", "Pr_id": "11679", "ProductSort": "0", "RegisteredFee": "0.00", "Remark": "", "ServiceCnName": "华邮宝平邮", "ServiceCode": "PK0218", "ServiceEnName": "EYBPYC", "TotalFee": "64.25", "Traceability": "Y", "VolumeCharge": "", "m_ServiceCode": "PK0218"}, {"ChargeWeight": "1.0", "Ef

```

```

fectiveness":"7-20","FreightCostFee":"","FreightFee":"53.00","FuelFee":
"0.00","InsuranceFee":"0.00","OtherFee":"0.00","Pr_id":"11645","ProductSo
rt":"0","RegisteredFee":"20.00","Remark":"1、带电货物需分开下单，分开交货2、
本渠道适用于带内置电池产品，包括手机、平板电脑、笔记本电脑、数码相机、电子表、蓝
牙键盘、多功能闹钟、无线路由器、电子烟（不含烟油等液体）等内置锂电池产品；3、面
单要求：10CM*10CM,面单要干净整洁，条码精度要大于300DPI，须用自粘型热敏纸张打印
面单。","ServiceCnName":"深圳挂号(纽扣电)","ServiceCode":"PK0079","ServiceE
nName":"SZGHNKDC","TotalFee":"73","Traceability":"Y","VolumeCharge":"","m
_ServiceCode":"PK0079"},{"ChargeWeight":"1.0","Effectiveness":"7-20","Fre
ightCostFee":"","FreightFee":"53.00","FuelFee":"0.00","InsuranceFee":"0.0
0","OtherFee":"0.00","Pr_id":"11656","ProductSort":"0","RegisteredFee":"2
0.00","Remark":"1、带电货物需分开下单，分开交货2、本渠道适用于带内置电池产品，
包括手机、平板电脑、笔记本电脑、数码相机、电子表、蓝牙键盘、多功能闹钟、无线路由
器、电子烟（不含烟油等液体）等内置锂电池产品；3、面单要求：10CM*10CM,面单要干净
整洁，条码精度要大于300DPI，须用自粘型热敏纸张打印面单。","ServiceCnName":"线
上-深圳挂号(WISH)","ServiceCode":"XSSZGHCP","ServiceEnName":"XSSZGHCP","To
talFee":"73","Traceability":"Y","VolumeCharge":"","m_ServiceCode":"XSSZGH
CP"},{"ChargeWeight":"1.0","Effectiveness":"3-25","FreightCostFee":"","Fr
eightFee":"53.00","FuelFee":"0.00","InsuranceFee":"0.00","OtherFee":"1.0
0","Pr_id":"11677","ProductSort":"0","RegisteredFee":"20.00","Remark":"","
","ServiceCnName":"华邮宝挂号","ServiceCode":"PK0219","ServiceEnName":"EYBGH
C","TotalFee":"74","Traceability":"Y","VolumeCharge":"","m_ServiceCode":
"PK0219"},{"ChargeWeight":"1.0","Effectiveness":"3-11","FreightCostFee":
":"","FreightFee":"65.00","FuelFee":"0.00","InsuranceFee":"0.00","OtherFee"
:"0.00","Pr_id":"10616","ProductSort":"0","RegisteredFee":"15.00","Remar
k":"1、限重：0-2公斤，面单的有效期限是15天，面单尺寸10CM*10CM;2、申报价值：如实
填写申报价值，如因申报价值与实际不符带来的风险由发货人承担；3、跟踪查询网站:htt
p://www.hh-exp.com/","ServiceCnName":"广州e邮宝","ServiceCode":"PK0114","S
erviceEnName":"GDEUBC","TotalFee":"80","Traceability":"Y","VolumeCharge":
":"","m_ServiceCode":"PK0114"},{"ChargeWeight":"1.0","Effectiveness":"","Fr
eightCostFee":"","FreightFee":"65.00","FuelFee":"0.00","InsuranceFee":"0.
00","OtherFee":"0.00","Pr_id":"10993","ProductSort":"0","RegisteredFee":
"15.00","Remark":"","ServiceCnName":"湖南e邮宝","ServiceCode":"PK0249","Se
rviceEnName":"HNEUBC","TotalFee":"80","Traceability":"N","VolumeCharge":
":"","m_ServiceCode":"PK0249"},{"ChargeWeight":"1.0","Effectiveness":"","Fr
eightCostFee":"","FreightFee":"65.00","FuelFee":"0.00","InsuranceFee":"0.
00","OtherFee":"0.00","Pr_id":"11059","ProductSort":"0","RegisteredFee":
"15.00","Remark":"","ServiceCnName":"深圳e邮宝(美国)","ServiceCode":"PK010
7","ServiceEnName":"szeubdUS","TotalFee":"80","Traceability":"N","VolumeC
harge":"","m_ServiceCode":"PK0107"},{"ChargeWeight":"1.0","Effectiveness"
:"7-20","FreightCostFee":"","FreightFee":"65.00","FuelFee":"0.00","Insura
nceFee":"0.00","OtherFee":"0.00","Pr_id":"9589","ProductSort":"0","Regist
eredFee":"15.00","Remark":"1、以色列e邮宝限重3Kg，其他国家e邮宝限重2Kg。2、发
往美国/新西兰/巴西/日本/哈萨克斯坦的e邮宝邮件，重量不足50g将按50g收费。3、发往
乌克兰的e邮宝邮件，重量不足10g将按10g收费，4、面单的有效期限是15天，面单尺寸10CM*
10CM。深圳e邮宝Plus","ServiceCnName":"深圳e邮宝Plus","ServiceCode":"PK0164"

```

```

, "ServiceEnName": "SZEYBPLUSC", "TotalFee": "80", "Traceability": "Y", "VolumeCharge": "", "m_ServiceCode": "PK0164"}, {"ChargeWeight": "1.0", "Effectiveness": "7-20", "FreightCostFee": "", "FreightFee": "65.00", "FuelFee": "0.00", "InsuranceFee": "0.00", "OtherFee": "0.00", "Pr_id": "9590", "ProductSort": "0", "RegisteredFee": "15.00", "Remark": "", "ServiceCnName": "深圳e邮宝Plus(带电)", "ServiceCode": "PK0212", "ServiceEnName": "SZEUBPLUSC", "TotalFee": "80", "Traceability": "Y", "VolumeCharge": "", "m_ServiceCode": "PK0212"}, {"ChargeWeight": "1.0", "Effectiveness": "3-15", "FreightCostFee": "", "FreightFee": "65.00", "FuelFee": "0.00", "InsuranceFee": "0.00", "OtherFee": "0.00", "Pr_id": "10019", "ProductSort": "0", "RegisteredFee": "15.00", "Remark": "", "ServiceCnName": "深圳e邮宝-特货", "ServiceCode": "PK0203", "ServiceEnName": "SZEUBTHC", "TotalFee": "80", "Traceability": "Y", "VolumeCharge": "", "m_ServiceCode": "PK0203"}, {"ChargeWeight": "1.0", "Effectiveness": "", "FreightCostFee": "", "FreightFee": "65.00", "FuelFee": "0.00", "InsuranceFee": "0.00", "OtherFee": "0.00", "Pr_id": "10436", "ProductSort": "0", "RegisteredFee": "15.00", "Remark": "", "ServiceCnName": "郑州e邮宝", "ServiceCode": "ZZEUB", "ServiceEnName": "ZZEUB", "TotalFee": "80", "Traceability": "Y", "VolumeCharge": "", "m_ServiceCode": "ZZEUB"}, {"ChargeWeight": "1.0", "Effectiveness": "3-12", "FreightCostFee": "", "FreightFee": "69.92", "FuelFee": "0.00", "InsuranceFee": "0.00", "OtherFee": "0.00", "Pr_id": "8635", "ProductSort": "0", "RegisteredFee": "21.50", "Remark": "1、限重0-2kg2、尺寸要求：长、宽、高长度之和<90cm，最长一边长度<60cm3、面单要求：10CM*10CM,面单要求干净整洁，不能出现中文字样以及MADE IN CHINA4、详细请查看报价表", "ServiceCnName": "华翰航空小包挂号", "ServiceCode": "PK0089", "ServiceEnName": "HHJJXBGHC", "TotalFee": "91.42", "Traceability": "Y", "VolumeCharge": "", "m_ServiceCode": "PK0089"}, {"ChargeWeight": "1.000", "Effectiveness": "3-15", "FreightCostFee": "", "FreightFee": "80.00", "FuelFee": "0.00", "InsuranceFee": "0.00", "OtherFee": "0.00", "Pr_id": "9721", "ProductSort": "0", "RegisteredFee": "15.00", "Remark": "", "ServiceCnName": "美国专线", "ServiceCode": "PK0220", "ServiceEnName": "USZX", "TotalFee": "95", "Traceability": "Y", "VolumeCharge": "7000", "m_ServiceCode": "PK0220"}, {"ChargeWeight": "1.0", "Effectiveness": "", "FreightCostFee": "", "FreightFee": "100.00", "FuelFee": "0.00", "InsuranceFee": "0.00", "OtherFee": "0.50", "Pr_id": "10506", "ProductSort": "0", "RegisteredFee": "0.00", "Remark": "", "ServiceCnName": "美国经济专线平邮-普货", "ServiceCode": "PK0240", "ServiceEnName": "USJJZXPYPHC", "TotalFee": "100.5", "Traceability": "N", "VolumeCharge": "", "m_ServiceCode": "PK0240"}, {"ChargeWeight": "1.0", "Effectiveness": "3-15", "FreightCostFee": "", "FreightFee": "108.00", "FuelFee": "0.00", "InsuranceFee": "0.00", "OtherFee": "0.50", "Pr_id": "10023", "ProductSort": "0", "RegisteredFee": "0.00", "Remark": "1、限重0-2kg2、尺寸要求：长、宽、高长度之和<90cm，最长一边长度<60cm3、面单要求：10CM*10CM,面单要求干净整洁，不能出现中文字样以及MADE IN CHINA4、详细请查看报价表", "ServiceCnName": "华翰航空小包平邮", "ServiceCode": "PK0084", "ServiceEnName": "HH ECONOMIC AIR MAIL - BATTERY", "TotalFee": "108.5", "Traceability": "Y", "VolumeCharge": "", "m_ServiceCode": "PK0084"}, {"ChargeWeight": "1.0", "Effectiveness": "", "FreightCostFee": "", "FreightFee": "110.00", "FuelFee": "0.00", "InsuranceFee": "0.00", "OtherFee": "0.50", "Pr_id": "10508", "ProductSort": "0", "RegisteredFee": "0.00", "Remark": "", "ServiceCnName": "美国经济专线平邮-特货", "ServiceCode": "PK0239", "ServiceEnName":

```

```
"USJJZXPINGYTH", "TotalFee": "110.5", "Traceability": "N", "VolumeCharge": "",
"m_ServiceCode": "PK0239"}, {"ChargeWeight": "1.0", "Effectiveness": "7-20", "FreightCostFee": "", "FreightFee": "330.00", "FuelFee": "0.00", "InsuranceFee": "0.00", "OtherFee": "0.00", "Pr_id": "8817", "ProductSort": "0", "RegisteredFee": "0.00", "Remark": "", "ServiceCnName": "深圳e邮宝-大货", "ServiceCode": "PK0211", "ServiceEnName": "SZEUBBIGC", "TotalFee": "330", "Traceability": "Y", "VolumeCharge": "", "m_ServiceCode": "PK0211"}], "time_cost(s)": "2.5156409740448"}
</response>
</ns1:callServiceResponse>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask": "Failure", "message": "试算失败.", "time_cost(s)": "0.28126621246338"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
data	Object	数据内容(2维数组)
Error	Object	参考公共请求参数中Error格式

data参数:

参数名	数据类型	说明
ChargeWeight	float	计费重量

参数名	数据类型	说明
Effectiveness	string	时效
FreightCostFee	float	（占位用）
FreightFee	float	运费
FuelFee	float	燃油费
InsuranceFee	float	保险费
OtherFee	float	其他费用
Pr_id	int	（占位用）
ProductSort	int	产品排序权重值
RegisteredFee	float	挂号费
Remark	string	备注
ServiceCnName	string	服务中文名称
ServiceCode	string	产品代码
ServiceEnName	string	服务英文名称
TotalFee	float	总费用
Traceability	string	可追踪
VolumeCharge	float	体积重计费
m_ServiceCode	string	（占位用）

interceptOrder （拦截订单）

简要描述：

拦截订单接口

service名称:

interceptOrder

paramsJson示例：

```
{
  "reference_no": "HHWDE0092000008YQ"
}
```

paramsJson参数:

参数名	数据类型	是否必填	说明
-----	------	------	----

reference_no	string	Require	系统运单号order_code。注：只有“已预报”状态支持拦截。
--------------	--------	---------	----------------------------------

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Success","message":"Success","reference_no":"HHWDE0098000004YQ","time_cost(s)":"0.28801608085632"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

```
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Failure","message":"订单不存在","reference_no":"HHWDE0098000004Y3Q","Error":{"errMessage":"订单不存在","errCode":"5000"},"time_cost(s)":"0.27701592445374"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
reference_no	Object	系统单号

Error	Object	参考公共请求参数中Error格式
-------	--------	------------------

getOrderFee (订单费用查询)

简要描述：

订单费用查询接口

service名称:

getOrderFee

paramsJson示例：

```
{
  "reference_no": "HHWFL9289000004YQ"
}
```

paramsJson参数:

参数名	数据类型	是否必填	说明
reference_no	string	Require	客户单号reference_no（或者系统运单号order_code，或服务商单号shipping_method_no都可以），注意：目前只支持单个单号查询

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask": "Success", "message": "Success", "reference_no"
```



```
: "HHWFL9289000004YQ", "data": { "total_price": "0.00", "details": [ { "fee_name": "\u901f\u9012\u8fd0\u8d39", "price": "25.50", "currency": "RMB", "create_date": "2019-10-16 11:20:12"}, { "fee_name": "\u6d4b\u8bd5\u8d39\u7528", "price": "0.07", "currency": "RMB", "create_date": "2019-10-16 11:20:12"}, { "fee_name": "\u6302\u53f7\u8d39", "price": "21.35", "currency": "RMB", "create_date": "2019-10-16 11:20:12"} ] }, "time_cost(s)": "0.3000168800354" }</response>
</ns1:callServiceResponse>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{ "ask": "Failure", "message": "Failure", "reference_no": "HHWFL9289000004YQ1", "Error": { "errCode": "50010", "errMessage": "订单不存在, 或运单不属于该客户"}, "time_cost(s)": "0.28201603889465" }</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
reference_no	string	客户参考号
data	Object	数据内容(2维数组)
Error	Object	参考公共请求参数中Error格式

data参数:

参数名	数据类型	说明
total_price	float	总费用

getOrderFee (订单费用查询)

参数名	数据类型	说明
details	Object	费用明细列表

details参数:

参数名	数据类型	说明
fee_name	string	费用名称
price	float	金额
currency	string	币种
create_date	string	创建时间

getBillingWeight (获取订单实际计费重)

简要描述：

订单实际计费重接口

service名称:

getBillingWeight

paramsJson示例：

```
{ "codes": [ "HHWIK1102001476YQ", "LY735983048CN" ] }
```

paramsJson参数:

参数名	数据类型	是否必填	说明
codes	Object/Array	Require	客户单号reference_no（或者系统运单号order_code，或服务商单号shipping_method_no 都可以）

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask": "Success", "message": "Success", "Data": [{"Code": "HHWIK1102001476YQ", "chargeweight": "0.301", "message": ""}, {"Code": "LY735983048CN", "chargeweight": "1.000", "message": ""}], "time_cost(s)": "0.078124046325684"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Success","message":"Success","Data":[{"Code":"HHWHL1092000002YQ","chargeweight":"","message":"订单还未入库"}, {"Code":"RV561160645CN11","chargeweight":"","message":"订单不存在,或运单不属于该客户"}],"time_cost(s)": "0.15624809265137"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
Data	Object	数据内容(2维数组)
Error	Object	参考公共请求参数中Error格式

Data参数:

参数名	数据类型	说明
Code	string	单号
chargeweight	float	计费重 (KG)
message	string	报错信息

getLastTrackCode(PDD专用-获取派送商信息)

简要描述：

查询运单入库后实际发货跟踪号以及尾端派送商信息接口

service名称:

getLastTrackCode

paramsJson示例：

```
{
  "reference_no": [ "MGP2211270106791", "HHWEW0007000009YQ" ]
}
```

paramsJson参数:

参数名	数据类型	是否必填	说明
reference_no	Object	Require	客户单号reference_no（或者系统运单号order_co 数组,如{" reference_no ":["code1"," code2"]}

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>
        {"ask":"Success","data":[{"state":"1","OrderNumber":"MGP2211270096505","TrackingNumber":"9214490209140407692148","providerCode":"U  
SPS","WayBillNumber":"HHWPQ2331002577YQ"}, {"state":"1","OrderNumber":"MGP2211270106791","TrackingNumber":"9214490209140406132133","providerCode":
```

```
"USPS","WayBillNumber":"HHWPQ2331003670YQ"}]], "Error":[], "message":"全部获取成功", "time_cost(s)": "0.07031512260437"}
</response>
</ns1:callServiceResponse>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>
        {"ask":"Failure","data":[{"state":"0","OrderNumber":"HHWPQ2331002577YQ1","TrackingNumber":"","WayBillNumber":"","msg":"单号：[HHWPQ2331002577YQ1]订单信息不存在"}, {"state":"0","OrderNumber":"MGP221127010679111","TrackingNumber":"","WayBillNumber":"","msg":"单号：[MGP221127010679111]订单信息不存在"}]], "Error":[], "message":"全部获取失败", "time_cost(s)": "0.028321027755737"}
      </response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
data	Object	数据内容(2维数组)
Error	Object	参考公共请求参数中Error格式

data参数:

参数名	数据类型	说明
state	int	1为成功；0为失败

参数名	数据类型	说明
OrderNumber	string	客户单号
TrackingNumber	string	跟踪号
providerCode	string	尾端轨迹服务商代码
WayBillNumber	string	系统运单号
msg	string	错误信息

getCargoTrackPdd(PDD专用-轨迹查询)

简要描述：

轨迹查询接口

service名称:

getCargoTrackPdd

paramsJson示例：

```
{
  "codes": [ "HHWDE9344000011YQ", "HHWDE9344000012YQ" ]
}
```

paramsJson参数:

参数名	数据类型	是否必填	说明
codes	Object/Array	Require	服务商单号shipping_method_no（或者系统订单号c 数组,如{"codes":["TFL1","TFL2"]}

注：1、此单号为创建订单时候我司返回的运单号或者追踪单号或者客户单号）

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Success","message":"Success","Data":[{"Code":"HHWQV2359000002YQ","Country_code":"US","New_date":"2022-12-25 14:26:15","Time_zone":"+08:00","New_Comment":"快件到达作业中心","Status":"AF","Err
```



```
or_code":"0000","Detail":[{"Occur_date":"2022-12-25 14:26:15","Occur_time_zone":"+08:00","Status":"AF","Comment":"Has entered the warehouse","track_area":"SHENZHEN"}, {"Occur_date":"2022-12-25 14:07:43","Occur_time_zone":"+08:00","Status":"IR","Comment":"Shipment information received","track_area":"CHINA"}]], "Error":[], "time_cost(s)":"0.032227039337158"}</response>
</ns1:callServiceResponse>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Success","message":"Success","Data":[{"Code":"Haaaaaaaa000002YQ","Country_code":"","New_date":"","New_Comment":"","Status":"","Error_code":"0001","Detail":[]}], "Error":[], "time_cost(s)":"0.030274868011475"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Failure","message":"","Data":[], "Error":{"cnMessage":"单号不能为空","enMessage":"Order Code. can not be empty"}, "time_cost(s)":"0.063003063201904"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数

参数名	数据类型	说明
message	string	参考公共请求参数中response参数
Data	Object	数据内容(2维数组)
Error	Object	参考公共请求参数中Error格式

Data参数:

参数名	数据类型	说明
Code	string	单号
Country_code	string	目的国家代码
New_date	string	最新的轨迹时间+时区，格式为：YYYY-MM-DD HH:MM:SS
Time_zone	string	时区，格式：+08:00
New_Comment	string	最新的轨迹内容
Status	string	轨迹状态码
Detail	Object	轨迹明细内容(2维数组)

Detail参数:

参数名	数据类型	说明
Occur_date	string	轨迹发生时间
Occur_time_zone	string	时区，格式：+08:00
Status	string	轨迹状态
Comment	string	轨迹内容
track_area	string	发生地点全称

轨迹状态代码对应表:

轨迹状态码	节点中文描述	节点英文描述
IR	电子信息已收到	Shipment information received
AF	已入仓	Has entered the warehouse
DF	已出仓	Out warehouse
IA	已上网	Internet Access
WB	到达中转站	Arrived at Transit Facility
WD	离开中转站	Departed from Transit Facility
GG	已过港	Have a port
BG	已报关	Have out customs clearance
AP	已交航	Air Transport
QF	已起飞	Has been take off
LD	已落地	Have fall to the ground
QG	清关中	Customs clearance in progress
YG	已清关	Have customs clearance
YQ	已提取	Already extracted
DR	到达目的地	Destination Reached
CA	到达尾程承运商	arrived at last mile sorting center
CB	离开尾程承运商	Leaving the terminal transfer center
ND	运输中	Normal delivery
CC	派送妥投	Delivered
UE	退件	Untread Expressage
PB	到达待取	Arrival to be picked up
AC	清关异常	Abnormal customs clearance
FI	签收失败	Delivery failed
DS	已丢失	The package has been lost

createFbaOrder (创建FBA订单)

简要描述：

创建FBA订单接口（注意：小包不是调用此接口）

service名称:

createFbaOrder

paramsJson示例：

```
{
  "reference_no": "WWTEST202001084545a1",
  "shipping_method": "PK0331",
  "order_weight": 1,
  "length": 1,
  "width": 1,
  "height": 1,
  "Warehouse": {
    "consignee_countrycode": "US",
    "consignee_street": "19 N Long Ave",
    "consignee_street2": "",
    "consignee_street3": "",
    "consignee_doorplate": "101",
    "consignee_name": "Xiao Cai",
    "consignee_telephone": "958465448",
    "consignee_postcode": "60644-3224",
    "consignee_province": "Illinois",
    "consignee_city": "Chicago",
    "consignee_taxno": "TA2020181245",
    "consignee_email": "9586645845@qq.com",
    "warehouse_code": "EDE5"
  },
  "Shipper": {
    "shipper_countrycode": "CN",
    "shipper_province": "GUANGDONG",
    "shipper_city": "SHENZHEN",
    "shipper_street": "pinghu 55 SHENZHEN GUANGDONG",
    "shipper_postcode": "518000",
    "shipper_name": "hh cai",
  }
}
```

```

    "shipper_telephone": "9586458745",
    "shipper_mobile": "18011911234",
    "shipper_taxno": "FAFA8181AA"
  },
  "BoxArr": [
    {
      "fba_box_no": "FBA15GTZ23DZU00001",
      "box_weight": 2,
      "box_length": 3,
      "box_width": 4,
      "box_height": 5,
      "ItemArr": [
        {
          "invoice_cname": "zhongwenming",
          "invoice_ename": "yingwenming",
          "invoice_weight": 1,
          "invoice_quantity": 1,
          "invoice_unitcharge": 11,
          "invoice_currencycode": "USD",
          "hs_code": 1234567890,
          "invoice_url": "http://www.amz.com/invoice_url",
          "sku": "testsku",
          "material": "glass",
          "invoice_function": "play",
          "ASIN": "ASINtestsku"
        },
        {
          "invoice_cname": "zhongwenming2",
          "invoice_ename": "yingwenming2",
          "invoice_weight": 1,
          "invoice_quantity": 2,
          "invoice_unitcharge": 22,
          "invoice_currencycode": "USD",
          "hs_code": 1234567890,
          "invoice_url": "http://www.amz.com/invoice_url",
          "sku": "testsku2",
          "material": "glass",
          "invoice_function": "play",
          "ASIN": "ASINtestsku2"
        }
      ]
    },
    {
      "fba_box_no": "FBA15GTZ23DZU00002",
      "box_weight": 2,

```

```
        "box_length": 3,
        "box_width": 4,
        "box_height": 5,
        "ItemArr": [
            {
                "invoice_cname": "zhongwenming",
                "invoice_ename": "yingwenming",
                "invoice_weight": 1,
                "invoice_quantity": 1,
                "invoice_unitcharge": 11,
                "invoice_currencycode": "USD",
                "hs_code": 1234567890,
                "invoice_url": "http://www.amz.com/invoice_url",
                "sku": "testsku",
                "material": "glass",
                "invoice_function": "play",
                "ASIN": "ASINtestsku"
            },
            {
                "invoice_cname": "zhongwenming2",
                "invoice_ename": "yingwenming2",
                "invoice_weight": 1,
                "invoice_quantity": 2,
                "invoice_unitcharge": 22,
                "invoice_currencycode": "USD",
                "hs_code": 1234567890,
                "invoice_url": "http://www.amz.com/invoice_url",
                "sku": "testsku2",
                "material": "glass",
                "invoice_function": "play",
                "ASIN": "ASINtestsku2"
            }
        ]
    }
}
```

paramsJson参数:

参数名	数据类型	是否必填	说明
reference_no	string	Require	客户参考号(客户自定义单号，不能重复，需唯一)
			配送方式（产品代码）

参数名	数据类型	是否必填	说明
shipping_method	string	Require	可以通过“获取配送方式”接口获取列表，也可以访问我司产品代码网站 https://www.hh-exp.cn/ProductCode/index.php 手工查询
country_code	string	Require	收件人国家二字母

extra_service	string	Option	附加服务代码，每个以英文分号“;”隔开
order_weight	float	Require	订单重量，单位KG
order_pieces	int	Option	外包装件数,默认1（ 小包默认值1即可 ，发FBA空海运等一票货多箱的时候才需要根据情况设置） 这个字段不是数量不要传错。
insurance_value	float	Option	投保金额，默认RMB
mail_cargo_type	string	Option	包裹申报种类（1-Gif礼品；2-CommercialSample商品货样；3-Document文件；4-Other其他。默认4）
length	float	Option	长，单位cm，默认1
width	float	Option	宽，单位cm，默认1
height	float	Option	高，单位cm，默认1
Warehouse	Object	Require	亚马逊收件仓地址信息
Shipper	Object	Require	发件人信息
BoxArr	Object/Array	Require	海关申报信息

Warehouse参数

参数名	数据类型	是否必填	说明
consignee_company	string	Option	收件人公司名

consignee_company	string	Option	收件人公司名
参数名	数据类型	是否必填	说明
consignee_province	string	Option	收件人省
consignee_city	string	Option	收件人城市
consignee_street	string	Require	收件人地址1

consignee_street2	string	Option	收件人地址2
consignee_street3	string	Option	收件人地址3
consignee_postcode	string	Option	收件人邮编
consignee_name	string	Require	收件人姓名
consignee_telephone	string	Option	收件人电话
consignee_mobile	string	Option	收件人手机
consignee_email	string	Option	收件人邮箱
consignee_certificatetype	string	Option	证件类型（ID-身份证；PP-护照）
consignee_certificatecode	string	Option	证件号码
consignee_credentials_period	string	Option	证件有效期， 格式：2014-04-15
consignee_doorplate	string	Option	收件人门牌号（ 注意：除一些特殊专线产品要求单独上传门牌号外，门牌号直接放地址里面即可无需单独放到此字段 ）
consignee_taxno	string	Option	收件人税号（VAT税号）
IOSS	string	Option	欧盟税号（ioss税号）
warehouse_code	string	Option	仓库代码(fab仓库代码)

Shipper参数

参数名	数据类型	是否必填	说明
-----	------	------	----

参数名	数据类型	是否必填	说明
shipper_company	string	Option	发件人公司名
shipper_countrycode	string	Require	发件人国家二字码

shipper_province	string	Require	发件人省
shipper_city	string	Require	发件人城市
shipper_street	string	Require	发件人地址
shipper_postcode	string	Require	发件人邮编
shipper_areacode	string	Option	区域代码
shipper_name	string	Require	发件人姓名
shipper_telephone	string	Require	发件人电话
shipper_mobile	string	Require	发件人手机
shipper_email	string	Option	发件人邮箱
shipper_fax	string	Option	发件人传真
order_note	string	Option	订单备注
shipper_taxno	string	Option	发件人税号（发件人VAT税号）

BoxArr参数

参数名	数据类型	是否必填	说明
fba_box_no	string	Require	FBA箱号
box_weight	string	Require	箱子重，单位kg
box_length	string	Require	箱子长，单位cm
box_width	string	Require	箱子宽，单位cm
box_height	string	Require	箱子高，单位cm

参数名	数据类型	是否必填	说明
ItemArr	Object	Require	详见ItemArr参数

ItemArr参数

参数名	数据类型	是否必填	说明
invoice_enname	string	Require	英文海关申报品名
invoice_cnname	string	Option	中文海关申报品名
invoice_weight	float	Require	申报重量，单位KG，精确到三位小数。
invoice_quantity	int	Require	数量
unit_code	string	Option	单位(MTR-米；PCE-件；SET-套)，默认PCE
invoice_unitcharge	float	Require	单价
invoice_currencycode	string	Option	申报币种，不传值默认为USD(美元)；USD-美元,AUD-澳元,CAD-加元,EUR-欧元,GBP-英镑,HKD-港币,MXN-墨西哥元,RMB-人民币,RUB-俄罗斯卢布,SGD-新加坡元
hs_code	string	Option	海关协制编号(海关编码)
invoice_note	string	Option	配货信息
invoice_url	string	Option	产品销售地址（销售链接）
sku	string	Option	产品SKU编码
material	string	Option	申报材质
invoice_function	string	Option	用途

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Success","message":"Success","reference_no":"WWTEST202001084545a5","shipping_method_no":"","order_code":"HHWAB424100005YQ","track_status":"2","sender_info_status":"0","ODA":"","agent_number":"10455768","parcels":[{"child_number":"HHWAB4241000005YQU001","fba_box_no":"FBA15GTZ23DZU00001","child_track_number":""},{ "child_number":"HHWAB4241000005YQU002","fba_box_no":"FBA15GTZ23DZU00002","child_track_number":""}], "time_cost(s)": "2.047544002533"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Failure","message":"服务异常：订单数据不合法","reference_no":"WWTEST202001084545","Error":{"errMsg":"参考单号已存在[WWTEST202001084545]","errCode":"ORDER_REFER_ISEXISTS"},"time_cost(s)": "0.92805314064026"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
reference_no	string	客户单号
shipping_method_no	string	服务商单号(追踪单号\尾程派送单号), 如: RV507879168CN ,默认取此单号

参数名	数据类型	说明
order_code	string	华翰系统订单号，系统生成的唯一单号，如：HHWCO0296000051YQ，如果需要华翰运单号， 可以获取这个字段， 此单号也可以17TRACK或华翰官网（hh-exp.com） 查询全程轨迹
track_status	string	track_status（1-已产生跟踪号，2-等待后续更新跟踪号,3-不需要跟踪号）——暂未启用此功能
sender_info_status	string	是否需要分配发件人地址（0-是，1-否）
ODA	string	是否需要ODA检验（Y-是）
parcels	Object	包含子单号，FBA箱号，子单追踪单号

agent_number	string	渠道换单号
Error	Object	参考公共请求参数中Error格式 (注意：获取报错信息是 message +errMessage 才是完整的报错提示)

batchGetDeliveryProof(批量获取发货证明)

简要描述：

批量获取标签接口

注：暂时批量获取发货证明的接口

service名称:

batchGetDeliveryProof

paramsJson示例：

```
{
  "reference_nos":["HHWAA4236000002YQ","HHWAA4236000001YQ"],
  "labelName": "发货证明"
}
```

paramsJson参数:

参数名	数据类型	是否必填	说明
reference_nos	object	Require	客户参考号（或者 系统运单号order_code 或服务商追踪号shipping_method_no ） 注意：一次性最多支持10票批量生成，超过数量容易出现获取失败或超时等错误，建议一次获取3票以内
labelName	string	Require	发货证明

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelo
```

```
pe/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Success","message":"Success","data":[{"url":
:"http://120.79.252.215:10001/PDF/1be397ef-901f-403d-a770-85a4dc30ee7.pdf",
"reference_no":"HHWCY4239000001YQ"},{"url":"http://120.79.252.215:1000
1/PDF/c06de41f-aa11-4f46-a941-299e7c1dd93d.pdf","reference_no":"HHWCY4237
000002YQ"}],"time_cost(s)":"0.11023712158203"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelo
pe/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Failure","message":"","Error":{"errCode":"","
,"errMessage":"全部获取失败"},"time_cost(s)":"0.10532593727112"}</response
>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
url	string	PDF标签格式URL地址
Error	Object	参考公共请求参数中Error格式

getFbaLabel(批量获取FBA标签)

简要描述：

批量获取FBA标签

注：批量获取FBA标签

service名称:

getFbaLabel

paramsJson示例：

```
{
  "box_nos": [ "HHWAA4236000002YQU0011" ]
}
```

paramsJson参数:

参数名	数据类型	是否必填	说明
box_nos	object	Require	FBA箱号（或者 子单追踪单号） 注意： 一次性最多支持20票批量生成， 超过数量容易出现获取失败或超时等错误

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask": "Success", "message": "Success", "data": [{"child_number": "HHWAA4236000002YQU001", "fba_box_no": "fbaboxnosjk11", "child_tra
```

```
ck_number":"HHWAA4236000002YQU001","ol_label_url_ori":"http://192.168.16.21:80/index/get-label/code/HHWAA1291000019YQ"}], "time_cost(s)":"0.13107204437256"}</response>
</ns1:callServiceResponse>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
  <SOAP-ENV:Body>
    <ns1:callServiceResponse>
      <response>{"ask":"Failure","message":"","Error":{"errCode":"","errMessage":"订单号HHWAA4236000002YQU0011不存在, 或者不属于该用户"},"time_cost(s)":"0.12351894378662"}</response>
    </ns1:callServiceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
data	Object	包含子单号, FBA箱号, 子单追踪单号, PDF标签URL
Error	Object	参考公共请求参数中Error格式

getWarehouseCode (获取仓库代码列表接口)

获取仓库代码列表接口

注：获取获取仓库代码列表

service名称:

getWarehouseCode

paramsJson示例 :

```
{
  "warehouse_code": "CDG7-60452"
}
```

paramsJson参数:

paramsJson不需要传参 默认查询所有 也支持查询单个

参数名	数据类型	是否必填	说明
warehouse_code	string	Option	仓库代码

response XML示例:

成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
  <SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
    <SOAP-ENV:Body>
      <ns1:callServiceResponse>
        <response>
          {
            "ask": "Failure",
            "data": [
              {
                "aa_id": "140",
                "aa_via_code": "AMZ-CDG7",
                "aa_warehouse_code": "CDG7-60452",
                "aa_status": "ON",
                "aa_contact": "PARC ACTIVITES DES PORTES DE SENLIS",
                "aa_country_code": "FR",
                "aa_province": "",
                "aa_city": "SENLIS",
                "aa_district": "",
                "aa_street": "1 AVENUE ALAIN BOUCHE R",
                "aa_street2": "",
                "aa_street3": "",
                "aa_doorplate": "",
                "aa_postcode": "6045"
              }
            ]
          }
        
```

```
2", "aa_telephone": "", "aa_mobile": "", "aa_company": "AMAZON FULFILLMENT CENT  
ER (CDG7)", "st_id_creator": "0", "createdate": "2023-09-01 13:47:35", "st_id_  
modify": "", "modifydate": "", "last_update_time": "2024-10-07 11:36:48", "grou  
p_code": "default", "service_warehouse_code": ""}], "Error": [], "message": "数据  
返回成功", "time_cost(s)": "0.092005968093872"}  
    </response>  
</ns1:callServiceResponse>  
</SOAP-ENV:Body>  
</SOAP-ENV:Envelope>
```

失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>  
  <SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/env  
elope/" xmlns:ns1="http://www.example.org/Ec/">  
    <SOAP-ENV:Body>  
      <ns1:callServiceResponse>  
        <response>  
          {"ask": "Failure", "data": [], "Error": [], "message": "暂无数据 ,  
不存在此仓库代码", "time_cost(s)": "0.10100603103638"}  
        </response>  
      </ns1:callServiceResponse>  
    </SOAP-ENV:Body>  
  </SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
aa_via_code	string	自定义代码
aa_warehouse_code	string	仓库代码
aa_status	string	状态,ON 生效, OF 失败
aa_contact	string	联系人
aa_country_code	string	国家
aa_province	string	州

aa_city 参数名	string 数据类型	城市 说明
aa_district	string	区
aa_street	string	街道1
aa_street2	string	街道2
aa_street3	string	街道3
aa_doorplate	string	门牌号
aa_postcode	string	邮编
aa_telephone	string	电话
aa_mobile	string	手机
aa_company	string	公司名
st_id_creator	string	创建人

createdate	string	创建时间
st_id_modify	string	修改人
modifydate	string	修改时间
group_code	string	仓库组别代码
service_warehouse_code	string	服务商仓库代码

register(注册用户接口 -未公开)

注册用户接口（暂未对外启用）

注：注册用户接口（暂未对外启用，使用之前请联系您的业务经理找我司IT获取请求参数信息）

service名称: (正式地址请咨询IT获取)

paramsJson示例：

```
{
  "verify_name": "test",
  "user_code": "test",
  "user_password": "123456",
  "user_name": "测试",
  "user_mobile_phone": "158138xx885",
  "customer_shortname": "华翰",
  "user_email": "1812@qq.com",
  "customer_address": "深圳市xxx",
  "customersource_code": "C",
  "sale_name": "WYZC11",
  "introducer_code": "DSERS"
}
```

Body参数:

参数名	数据类型	是否必填	说明
verify_name	string	Require	校验的对象名字 (请咨询IT获取)
user_code	string	Require	用户名
user_password	string	Require	密码
user_name	string	Require	联系人
user_mobile_phone	string	Require	联系人电话
customer_shortname	string	Require	客户名称/公司名称

参数名	数据类型	是否必填	说明
user_email	string	Require	邮箱
customer_address	string	Require	详细地址
customersource_code	string	Option	客户来源（C:自行寻找 P: 平台介绍 S:内部介绍 A:API注册(默认)）
sale_name	string	Require	绑定销售人员工号
introducer_code	string	Option	介绍人代码 （需提前找您的销售人员获取）

response 成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
  <SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
    <SOAP-ENV:Body>
      <ns1:callServiceResponse>
        <response>
          {"ask": "1", "message": "账号注册成功", "account": "test", "password": "123456", "customer_id": "15867", "time_cost(s)": "0.16000890731812"}
        </response>
      </ns1:callServiceResponse>
    </SOAP-ENV:Body>
  </SOAP-ENV:Envelope>
```

response 失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
  <SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
    <SOAP-ENV:Body>
      <ns1:callServiceResponse>
        <response>
          {"ask": 0, "message": "用户名已被使用", "time_cost(s)": "0.16000890731812"}
        </response>
      </ns1:callServiceResponse>
    </SOAP-ENV:Body>
  </SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数
message	string	参考公共请求参数中response参数
account	string	用户账号
password	string	用户密码
customer_id	string	用户ID

customerLeads (客户线索接口-未公开)

客户线索接口 (暂未对外启用)

注：客户线索接口（暂未对外启用，使用之前请联系您的业务经理找我司IT获取请求参数信息）

service名称: customerLeads

paramsJson示例：

```
{
  "customersource_code": "test",
  "company_name": "test",
  "contact_name": "123456",
  "contact_phone": "158138xx885",
  "province": "广东省",
  "city": "深圳市",
  "area": "龙岗区",
  "street": "布吉街道新二村202",
  "sale_name": "ADMIN",
  "remarks": "这个是个测试",
}
```

Body参数:

参数名	数据类型	是否必填	说明
customersource_code	string	Require	校验的客户来源名字 (请咨询IT获取)
company_name	string	Require	公司名称
contact_name	string	Require	联系人名字
contact_phone	string	Require	联系人电话
province	string	Require	省份
city	string	Require	城市

area 参数名	string 数据类型	Require 是否必填	地区 说明
street	string	Require	街道
sale_name	string	Option	业务员 默认admin
remarks	string	Option	客户备注

response 成功返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
  <SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
    <SOAP-ENV:Body>
      <ns1:callServiceResponse>
        <response>
          {"ask":"1","message":"success","customer_code":"HHTEST12122","time_cost(s)":"0.16000890731812"}
        </response>
      </ns1:callServiceResponse>
    </SOAP-ENV:Body>
  </SOAP-ENV:Envelope>
```

response 失败返回示例:

```
<?xml version="1.0" encoding="UTF-8"?>
  <SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="http://www.example.org/Ec/">
    <SOAP-ENV:Body>
      <ns1:callServiceResponse>
        <response>
          {"ask":"0","message":"公司名称已存在","time_cost(s)":"0.11800694465637"}
        </response>
      </ns1:callServiceResponse>
    </SOAP-ENV:Body>
  </SOAP-ENV:Envelope>
```

response参数:

参数名	数据类型	说明
ask	string	参考公共请求参数中response参数

message 参数名	string 数据类型	参考公共请求参数中response参数 说明
customer_code	string	客户代码